

Thermelt colours



The complete repair programme for the wood industry



Floors

Windows and doors

Glued wood

Furniture

BØGH CONSULT DENMARK A/S

Charles Lindberghs Vej 6, DK-9430 Vadum T: +45 9827 1919 - F: +45 9827 2081
E-mail: bcd@mail.tele.dk - www.boeghconsult.dk



Knot filler

If you have trouble repairing wood damages such as knots, scratches, wind lines etc. here is the solution. The product that can help you is the Thermelt Knot filler which is of polyamide base. It is especially developed for wood fillings because the wood and the filler works together.


Thermelt Knot filler is suitable for all wood sorts, soft or hard, light or dark as it is available in many colours and 3 hardnesses. The type and colour depends on the wood sort and which treatment the wood will receive later. We currently have 14 various colours/types that are all suitable for segments such as furniture, parquet, windows/doors and also for difficult repairs on edges and corners.

The 813 + 134 series are both flexible and can be cut with a chisel. This makes it easy to use in all types of productions as you do not need a big sanding machine to finish the repair.

The 162 series is hard and mostly used within the flooring industry due to its resistance towards pressure from spiked heels and general wear and tear etc.



Damaged knot



Repaired knot

300mm

12mm

Especially good for:

- Windows/doors
- Furniture
- Glued wood
- Parquet floors
- Formwork
- Difficult repairs such as edges and corners



See the Knot filler video at www.boeghconsult.dk


How to do



Apply the filler with a knot filler gun



Place a cooling iron on the repair area



Very short cooling time



After cooling



Remove the surplus filler with a chisel



The repair is ready for sanding / treatment

Important info



Always upright position



Never lay a warm gun on the side



The knot filler is packed in air tight bags containing 10 sticks.

The bag must be sealed very well after use.